



■ 通用型高频COG类多层片状陶瓷电容器  
GENERAL HIGH FREQUENCY COG MLCC

尺寸规格 Size Code	尺寸 Dimensions(mm)				工作电压 Rated Voltage	容量范围 Capacitance(pF)
	L	W	T	WB		(COG)NPO
0402	1.00±0.05	0.50±0.05	0.50±0.05	0.25±0.10	6.3V	0.2~470
					10V	0.2~470
					16V	0.2~470
					25V	0.2~470
					50V	0.2~220
					6.3V	0.3~1,000
0603	1.60±0.10	0.80±0.10	0.80±0.10	0.30±0.10	10V	0.3~1,000
					16V	0.3~1,000
					25V	0.3~1,000
					50V	0.3~1,000
					6.3V	0.5~2,700
					10V	0.5~2,700
0805	2.00±0.20	1.25±0.20	0.70±0.20 1.00±0.20 1.25±0.20	0.50±0.20	16V	0.5~2,700
					25V	0.5~2,700
					50V	0.5~2,200
					6.3V	0.5~5,600
					10V	0.5~5,600
					16V	0.5~5,600
1206	3.20±0.30	1.60±0.20	0.70±0.20 1.00±0.20 1.25±0.20	0.50±0.25	25V	0.5~5,600
					50V	0.5~4,700
					6.3V	10~10,000
					10V	10~10,000
					16V	10~10,000
					25V	10~10,000
1210	3.20±0.30	2.50±0.30	1.25±0.30 1.50±0.30	0.75±0.25	50V	10~7,500
					6.3V	10~10,000
					10V	10~10,000
					16V	10~10,000
					25V	10~10,000
					50V	10~6,800
1808	4.50±0.40	2.00±0.20	2.00	0.75±0.25	6.3V	10~15,000
					10V	10~15,000
					16V	10~15,000
					25V	10~15,000
					50V	10~10,000
					6.3V	10~47,000
1812	4.50±0.40	3.20±0.30	2.50	0.75±0.25	10V	10~47,000
					16V	10~47,000
					25V	10~47,000
					50V	10~27,000
					6.3V	10~100,000
					10V	10~100,000
2225	5.70±0.50	6.30±0.50	2.50	1.00±0.25	16V	10~100,000
					25V	10~100,000
					50V	10~47,000
3035	7.60±0.50	9.00±0.50	3.00	1.00±0.25		

备注：可根据客户的特殊要求设计符合客户需求的产品。  
Note: We can design according to customer special requirements.